

撒肥机 / FERTILIZER SPREADER

采用美国技术设计, 主要适用于农田耕前撒播底肥、耕后播种及草场、牧场的种肥混合撒播作业。配套马力 25~60 马力, 播幅 16M-30M。该机结构紧凑、性能优良、适用范围广、作业效率高、种肥撒播均匀等特点。

This fertilizer spreader is designed according to American technology. Fertilizer spreader is applicable for spreading fertilizer, sowing seeds and mixture of fertilizer and seeds, with 25-60 horsepower, 16M-30M sowing rate, compact structure, high performance, wide application, and high efficiency, uniform broadcast sowing, etc.



型号 Model	CDR-230	CDR-260	CDR-500	CDR-1000
工作幅宽 Width of spreader (m)	5-20			
肥箱容积 Capacity of fertilizer box (L)	230	260	480	950 - 1050
PTO 转速 PTO speed (r/min)	540			
整机重量 Weight (kg)	65	80	160	290
配套马力 Tractor power (hp)	18 - 30	30 - 40	50	90
挂接方式 Mounted cat	I 类三点悬挂 Cat I		II 类三点悬挂 Cat II	

喷雾机 / BOOM SPRAYER

3W 系列喷雾机主要用于大豆, 玉米, 棉花, 小麦, 水稻等旱田水田的施药, 同时也适用于草坪, 果树, 茶树, 蔬菜, 路旁树等药物喷洒工作。产品容量从 200L-1000L, 喷幅 6m-12m, 配套 12-120hp 拖拉机。

3W series of sprayer is suitable for spraying the medicament for the planter of bean, corn, cotton, grain. Also for lawn, fruit, vegetable, road side tree. The capacity could be 200L-1200L, the spraying width could be 6m-12m with 12-120hp tractor.



型号 Model	3W-200	3W-300	3W-400	3W-500	3W-700	3W-900	3W-1000
工作幅宽 Width of spraying (m)	6			10/12			
药箱容积 Case volume (L)	200	300	400	500	700	900	1000
PTO 转速 PTO speed (r/min)	540						
整机重量 Weight (kg)	80	90	130	240/270	310/340	350/380	380/400
配套马力 Tractor power (hp)	15	20-30	30-45	50-70	60-80	70-90	70-100
挂接方式 Mounted cat	三点悬挂 Three-point mounted						

农用拖车 / FARM TRAILER

该系列农用拖车主要配套于 30-50hp 四轮拖拉机, 适用于山地适用于平原、山区、沼泽、丘陵、农村以及公路运输各类散装货物, 该类车型结构牢固、造型美观、安全可靠、经久耐用。可分为自卸型和非自卸型。

The single axle farm trailer is used for 30-50hp 4-wheels tractor, applicable for transporting various bulk cargoes in plains, mountains, wetlands, knap, rural area and highway, with the feature of solid structure; beautiful, safe, reliable, durable. It is included in two types: dumping trailer and not dumping trailer.



型号 Model	车厢尺寸 Box size(mm) LxWxH	重量 Weight (kg)	轮胎 / 数量 Tyre / Q'ty	自卸 Dumping	配套马力 Power(hp)
7CX-1(E)	2000*1000*330	305	ST175/80D13	Back dumping	12-18
7CX-1.5(E)	2000*1000*360	332	ST175/80D13	Back dumping	12-18
7CX-2(E)	2500*1500*460	650	10.0/75 12PR	Back dumping	18-24
7CX-2(E)	2500*1500*460	620	7.50-16/2	Back dumping	18-24
7CX-2.5(E)	2500*1660*460	730	7.50-16/2	3 side dumping	24-30
7CX-3(E)	3200*1800*460	720	7.50-16/2	No dumping	24-30
7CX-3(E)	3100*1600*460	990	10.0/75-15.3 14PR/2	3 side dumping	24-30
7CX-3(E)	3100*1600*460	1260	10.0/75-15.3 6PR/4	3 side dumping	24-30
7CX-3(E)	3400*1700*460	1150	10.0/75-15.3 16PR/2	3 side dumping	24-30
7CX-3(E)	3400*1700*460	1000	10.0/75-15.3 16PR/2	Side dumping	24-30
7CX-3(E)	3400*1700*(460+460)	1160	10.0/75-15.3 16PR/2	Back dumping	24-30
7CX-4(E)	3400*2000*(460+460)	1325	11.5/80-15.3 16PR/2	3 side dumping	24-30
7CX-5(E)	3700*1900*(460+460)	1350	400/60-15.5 14PR/2	Back dumping	40-50
7CX-5(E)	3700*1900*(460+460)	1420	400/60-15.5 14PR/2	3 side dumping	40-50
7CX-5(E)	4100*2100*550	1950	11.5/80-15.3 10PR/4	3 side dumping	50-60
7CX-5(E)	4100*2100*(550+550)	2165	11.5/80-15.3 10PR/4	3 side dumping	50-60
7CX-6(E)	5000*2200*550	1900	10.0/75-15.3-16PR/4	Side dumping	50-60
7C-7(E)	4100*2100*(460+460)	1700	10.0/75-15.3 16PR/4	No dumping	50-60
7CX-7(E)	4100*2100*(460+460)	2100	10.0/75-15.3 16PR/4	3 side dumping	50-60
7CX-8(E)	4100*2100*(550+550)	2315	11.5/80-15.3 16PR/4	3 side dumping	60-80
7CX-8(E)	4410*2010*1000	2000	11.5/80-15.3 16PR/4	3 side dumping	60-80